# pH/Temperature Meter

## MAKE YOUR JOB FASTER AND EASIER

Assess the pH and the temperature



# **USER FRIENDLY AND EASY TO CALIBRATE**

This pocket digital pH/Temp Meter is designed for on-the-go measurements of pH and temperature. The high accuracy pen type pH/Temp meter uses combined pH electrode of high sensitivity, fast response, and good repetition as probe. It has a pH range from 0 to 14 with an accuracy of  $\pm 0.05$  pH.

#### **Product Features**

- 1. Big LCD with dual display
- 2. pH/Temperature dual display
- 3. Measuring stability indicator
- 4. One touch auto-calibration up to 3 points
- 5. Calibration values are adjustable
- 6. Can keep sensor wet & last life time















## **Package Contains**

- 1. The meter x 1
- 2. LR44 button battery x 4
- 3. Operation manual



### **Product Information**

| Code    | Model | pH Range   | pH Accuracy | pH Resolution | Temp. Range | Temp. Accuracy | Operating Temp. | Operating RH% |
|---------|-------|------------|-------------|---------------|-------------|----------------|-----------------|---------------|
| 9318522 | 8686  | 0.00~14.00 | +/-0.05     | 0.01          | 0~60.0°C    | +/-0.5°C       | 0~50°C          | Humidity <80% |

#### **EMAUX WATER TECHNOLOGY CO., LTD**

ADDRESS: Flat A-D, 20/F., Kai Bo 22, 22 Wing Kin Road,

Kwai Chung, Hong Kong PHONE +852 2832 9880 www.emauxgroup.com

**•** YOUR PREMIER SUPPLIER

Available from:

# Digital Water Quality Meters

QUICK RESPONSE AND EASY TO CALIBRATE



**Pool & Spa Equipment** 

2 Glass balls ph sensor

# Salinity Meter

# SIMPLE TO USE, ECONOMICAL PEN TYPE METER

Assess the concentration of salt





## **Package Contains**

- 1. The meter x 1
- 2. LR44 button battery x 4
- 3. Operation manual

# QUICK RESPONSE AND EASY TO CALIBRATE

This pocket digital Salinity Meter is designed for the pool professional for testing the salt level in pools using salt chlorinators. The meter is dipped into pool water to get instant measurements from a range of 0 to 70 ppt (0 - 70,000ppm) at temperatures from 0 - 50°C.

#### **Product Features**

- 1. Dual display Temp. & Salinity with ATC
- 2. Waterproof membrane keypad
- 3. Low cost and high accuracy
- 4. Built-in NaCL Temp. coefficient
- 5. Built-in NaCL Cond. to TDS conversion factor
- 6. Auto power off / Non-Sleep mode disable
- 7. Big LCD dual display
- 8. Auto temperature compensation
- 9. One touch auto-calibration
- 10. Data hold function
- 11. Calibration information review
- 12. Low battery indicator



#### **Product Information**

| Code    | Model | Salinity Range | Accuracy   | Salinity Resolution | Temperature Range | Operating RH%  |
|---------|-------|----------------|--|---------------------|-------------------|----------------|
| 9316635 | 8371  |                | +/-1%F.S +/- 1 digit 1ppm or 0.01ppt<br>+/-2%F.S +/- 1 digit (10.1~70.0 ppt) |                     | 0~50.0°C          | Humidity < 80% |

# **ORP** Meter

## BIG DISPLAY FOR EASY READING

Assess the ORP (Oxidation-Reduction Potential)



### **Package Contains**

- 1. The meter x 1
- 2. LR44 button battery x 4
- 3. Operation manual

# EASY TO USE AND FACTORY CALIBRATED

ORP Meter ideal for use in swimming pools and spas, as it can provide a valuable indication of water quality. The size is small and easy to carry with. Simple to use and provides instant display of results.

#### **Product Features**

- 1. Big LCD with real time ORP display in mV
- 2. Storage solution bottle to keep sensor wet & last life time

Application: - excellent to use in the water disinfection process

- excellent to use in the aquaculture













What is ORP? \_\_\_

ORP is a term used frequently in the water treatment & food processing industry. ORP stands for Oxidation-Reduction Potential, which measures the cleanliness of the water & its ability to break down contaminants.



#### **Product Information**

| Code    | Model | mV Range          | mV Accuracy | mV Resolution | Operating Temp. | Operating RH% | Storage Temp. | Storage RH%   |
|---------|-------|-------------------|-------------|---------------|-----------------|---------------|---------------|---------------|
| 9318521 | 8552  | -999mV~<br>+999mV | +/- 4mV     | 1mV           | 0~60.0°C        | Humidity <80% | -10~60°C      | Humidity <90% |

ORP Meter ORP Meter