Galaxy Single-Element Cartridge Filter



Pool & Spa Equipment

Product Features

Deliver Optimal Sparkling Clear Water

Galaxy Single-Element Cartridge Filter is built with high-strength and UV-resistant material to prolong the product life. The compact and low height design is suitable for any pool especially with limited system setup space. The extensive dirt-catching capability of the filter element makes this filter highly efficient. A reliable choice for crystal clear water.







User friendly

- 4 x mounting holes
- Easy-grip lid handle
- Indicative pressure gauge tells you when to service
- Knee-height tank base facilitates easy cartridge replacement

Trouble-free maintenance

- Locking ring with quick-release latch allows removing and installing the top tank quickly.
- Large water drain makes fast and easy winterisaton.
- Simple cleaning and rinsing the filter element with a garden hose.

Eco-Friendly

Big one-piece cartridge element provides a large filtration surface for trapping more dirt and debris. Less cleaning required, and unlike sand filters, needs no backwashing thus saving water and its precious chemicals.



Product Information:

Pool Type	Code	Model with Standard Element	Code	Model with Anti-microbial Element	Filter Area		Flow Velocity		Max Flow Rate		In / Outlet Connections		Α	В	С	D	Е	F	
					ft²	m ²	gpm/ft²	m³/h/m²	gpm	lpm	m³/h	GB(mm)	ANSI	mm	mm	mm	mm	mm	mm
Residential	9140401	ICF100	9140409	ICF100S	100	9.29	1.0	2.443	100	379	22.7	GB50	1.5"/2"		444.5	588	304	335	91
												GB63	2"/2.5"						
	9140402	ICF150	9140410	ICF150S	150	13.94	0.8	1.955	120	454	27.2	GB50	1.5"/2"	910	444.5	588	304	335	91
												GB63	2"/2.5"						
	9140403	ICF200	9140411	ICEDOOC	200	18.58	0.6	1.466	120	454	27.2	GB50	1.5"/2"	1022	3 444.5	588	304	335	91
				ICF200S								GB63	2"/2.5"						
Public .	9140401	ICF100	9140409	ICE100C	100	0.20	0.275	0.917	38	144	8.6	GB50	1.5"/2"		444.5	588	304	335	91
				ICF100S	100	9.29	0.375					GB63	2"/2.5"						
	9140402	2 ICF150	9140410	1651506	150	13.94	0.375	0.917	56	6 212	2 12.7	GB50	1.5"/2"	- 010 1	444.5	588	304	335	91
				ICF150S								GB63	2"/2.5"						
	9140403	3 ICF200	9140411	ICEDOOS	200	18.58	0.375	0.917	7.5	284	17	GB50	1.5"/2"	1022	3 444.5	588	304	225	01
				ICF200S					75			GB63	2"/2.5"					335	91

NOTE


Based on Industry standard:

Cartridge Filter Element:

Code	Model (Standard)	Code	Model (Anti-microbial Element)	G mm	H mm	Micron µm	Fold Number
914100004	ICF100-CE		ICF100S-CE				137
914100005	ICF150-CE	914100019	ICF150S-CE	590	Ø267	15	172
914100006	ICF200-CE	914100020	ICF200S-CE	717	Ø267	15	187

Galaxy Series Filter is equipped with:

- 1. universal standard of union connection
- 2. pressure gauge 3. cartridge filter element



The maximum flow velocity for residential pools is 1 GPM/ft², with a maximum flow rate of 120 GPM; For public
pools, the maximum flow velocity is 0.375 GPM/ft², with a maximum flow rate of 150 GPM.

Determined by pump size and piping system hydraulics; 2" piping is recommended for flow rates equal to or greater than 90 GPM (341 LPM).

EMAUX WATER TECHNOLOGY CO., LTD

2/F, Lockhart Centre, No. 301-307 Lockhart Road, Wanchai, Hong Kong PHONE +852 2832 9880 www.emauxgroup.com



Available from:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
© FMAUX WATER TECHNOLOGY CO., LTD, ALL RIGHTS RESERVED.